

Technical Specification Lotus 2-Eleven

ABS
Ligh
Yoko
Ligh
Tool

Model	Lotus 2-Eleven
Launch Edition	UK Single Vehicle Approval (SVA) option including all front and rear lights, catalyst, single-plane rear wing and other items to achieve compliance with UK road legal requirements OR
	Track Only option with high downforce single plane carbon fibre rear wing, high down force front splitter, brake lights and rear indicators, FIA approved driver's race seat BOTH AVAILABLE AS LEFT OR RIGHT HAND DRIVE
Engine	2ZZ-GE engine, Metal Matrix Composite (MMC) & aluminium lightweight and compact construction. Chain driven Double Over- Head Camshafts (DOHC) exploiting a Variable Valve Timing & Lift- intelligent (VVTL-i) system. Lotus T4e engine management system, multi-point sequential fuel injection, electronic ignition and electronic throttle control. Lotus Sport developed supercharger installation with unique rear mounted air to air intercooler
Emissions	Three-way catalytic converter (UK SVA option only). Full On-Board Diagnostics (OBD)
Transmission	C64 manual transaxle, aluminium lightweight construction. 6-speed, close ratio, constant mesh helical gears. Uprated clutch plate and cover
Chassis	Unique high-sided variant of the Lotus Elise lightweight structure of epoxy bonded aluminium alloy extrusions. Glass fibre composite front crushable structure, 6-point FIA compliant rollover structure with integral harness mounts and lightweight galvanised steel rear sub frame
Aerodynamic Aids	Low profile body to reduce drag, coupled with a large front splitter, rear diffuser and SVA compliant rear wing (SVA option) or carbon fibre GT3-inspired rear wing (track option) to produce noticeable downforce at speed
Body	Ultra-lightweight (40 kg/88 lbs) composite body featuring core-mat technology. All external panels bolted on for ease of removal and repair. A dynamic and unique three-way Lotus Sport colour scheme complete with exclusive decal pack. Lightweight tinted Perspex low profile wind deflector
Interior	UK SVA Option Unique Lotus Sport driver and passenger sports seats, both fitted with 4-point harness Track Only Option Lotus Sport Recaro FIA approved driver's race seat with 6-point harness. Sports passenger seat with 4-point harness UK SVA and Track Only Options – Common Items Variable traction control, starter button, light controls, handheld fire extinguisher, footwell divider, Lotus Sport build plate and leather trimmed steering wheel
Steering	Solidly mounted mechanical rack and pinion. 2.8 turns lock-to-lock
Suspension	Fully independent suspension utilising unequal length wishbones. Öhlins 2-way adjustable dampers with coil over springs. Lotus Sport adjustable front anti-roll bar. Rear double shear track control arm brace. Unique steering arms and front upper wishbones to suit ultra- low ride height

Wheels	Black Lotus Sport lightweight forged 5-spoke wheels. Front: 7Jx16 & Rear: 8Jx17
Tyres	Yokohama A048 R LTS. F: 195/50 R16 & R: 225/45 R17
Brakes	288 mm cross-drilled and ventilated discs. Aluminium alloy AP Racing 2-piston front calipers (available in yellow as an extra cost option), and Brembo single sliding piston at the rear. Pagid RS14 sports brake pads. High-grade slicone brake fluid. Stainless steel braided brake hoses. Servo assistance and track tuned ABS

Performance Data			
Max Power	255 PS (252 bhp/188 kW @ 8000 rpm		
Max Torque	242 Nm (179 lb/ft) @ 7000 rpm		
 Power to weight ratio 	380 bhp/tonne		
• 0-60 mph	3.8 secs est		
• 0-100 km/h	3.9 secs est		
• 0-100 mph (0-160 km/h)	9.1 secs est		
 Maximum speed 	155 mph (250 km/h)		
Vehicle mass - kerb	670 kg (1477 lbs) -SVA option		
Vehicle mass - kerb	666 kg est (1468 lbs)-Track Only		
	option		
 Weight distribution 	38% Front / 62% Rear		

Dimensions			
Wheelbase Track Overall length Overall width (door mirrors excluded) Overall width (door mirrors included) Overall width (door mirrors included) Overall height - mid-laden Overhang Ground clearance - mid-laden Luggage capacity	2300 mm F: 1457 mm & R: 1607 mm 3822 mm (SVA version) 1709 mm 1735 mm (Track version) 1112 mm 847 mm (SVA version) 90 mm Front / 100 mm Rear None		

Powertrain Specification		
• Engine installation	Transverse, mid-mounted	
• Cylinder configuration	In-line 4	
• Capacity	1796 cm ³	
• Bore / Stroke	82.0 mm / 85.0 mm	
Valve arrangement Compression ratio Twin Oil Coolers Engine oil accumulator unit Torque-sensing Limited Slip Differential (LSD)		
Lotus Sport limited slip differential (LSD)	None	
plate type	Standard on Launch Edition	
Lotus Traction Control System (TCS) Decat Pipe	Track Only option	

Vehicle Specification • Air conditioning None • Cross-drilled brake discs Standard on

ss-drilled brake discs	Standard on Launch Edition
with servo assisted brakes	Standard on Launch Edition
tweight Forged 5-spoke alloy wheels	Standard on Launch Edition
ohama Advan A048 LTS tyres	Standard on Launch Edition
t weight dry cell battery	Standard on Launch Edition
kit	Standard on Launch Edition
t weight dry cell battery	Standard on Launch Edition

Safety Specification			
 4-point driver and passenger harnesses. 	SVA Option Only		
6-point driver harness with 4-point passenger harness	Track Only option		
FIA compliant Lotus Sport Recaro race seat	Track Only option		
 6-point FIA compliant rollover structure with integral harness mounts 	Standard on Launch Edition		
Hand held fire extinguisher	Standard on Launch Edition		

Exterior Specification Launch edition exclusive three-way (Sport Standard on Launch Edition Black, Sport Silver, Sport Yellow) Lotus Sport colour scheme with exclusive decal pack Lightweight race side and central view mirror Standard on Launch Edition Black finish rear diffuser Standard on Launch Edition • Large Carbon Fibre Rear Wing Track Only option Large Front Splitter Track Only option Clear sill stone-chip protection film Standard on Launch Edition SVA compliant front and rear light pack SVA Option only · Rear indicators, brake and rain lamp Track Only option

Interior Specification		
 ProBax Lotus Sport seats Metallic Silver Side Panels Central door locking Lightweight aluminium foot-well divider Black plain/perforated leather steering wheel Black perforated leather gear-lever gaiter Polished aluminium par shift Polished aluminium handbrake sleeve Key ignition and steering lock Battery isolation switch Speedometer (mph or kph)/Rev counter Electrical equipment 	SVA option - Standard on Launch Edition Track Only option - Passenger only Standard on Launch Edition None Standard on Launch Edition Standard on Launch Edition UK SVA Option - Headlights, brake lights, front, side and rear indicators, fog light, reversing light, horn Track Only Option - Brake lights, rear indicators, rain lamp UK SVA and Track Only Options - Common Items - Variable traction control, starter button, lightweight dry cell battery, battery isolation	

The Lotus 2-Eleven and selected equipment fitted to this vehicle is not road legal in all markets. Customers should confirm requirements prior to order. Each customer is responsible for ensuring their car fully complies with the respective track/race regulations. Different service schedules and warranty conditions apply. This vehicle is not covered by the standard manufacturer's warranty. Lotus reserves the right to amend or change specifications and options at any time. Terms and conditions apply and are available on request. Lotus Sport is a trading name of Lotus Cars Ltd, registered address Potash Lane, Hethel, Norwich, Norfolk, NR14 8EZ, England.



www.lotussport.co.uk